





Bearing Driveshaft do Brasil



Cylindrical bore



Tapered bore



30 mm x 62 mm x 20 mm SKF 2206EKTN9 self aligning ball bearings

Bearing No. 2206EKTN9

2206EKTN9 Bearing 2D drawings and 3D CAD models

| | |
|-------------------------------|-------------|
| Size | 30x62x20 mm |
| Bore Diameter | 30 mm |
| Outer Diameter | 62 mm |
| Width | 20 mm |
| d | 30 mm |
| D | 62 mm |
| B | 20 mm |
| C | 20 mm |
| d2 | 38,8 mm |
| r1 min. | 1 mm |
| r2 min. | 1 mm |
| D1 | 55 mm |
| da min. | 35,6 mm |
| Da max. | 56,4 mm |
| ra max. | 1 mm |
| Weight | 0,26 Kg |
| Basic dynamic load rating (C) | 23,8 kN |
| Basic static load rating (C0) | 6,7 kN |
| Fatigue load limit (Pu) | 0,35 |
| Reference speed | 22000 r/min |
| Limiting speed | 15000 r/min |
| Calculation factor (e) | 0,33 |
| Calculation factor (kr) | 0,045 |
| Calculation factor (Y0) | 2 |
| Calculation factor (Y1) | 1,9 |



Bearing Driveshaft do Brasil